

SCR241

The Premier Mobile Computing Solution



Overview

The SCR241 smart card reader provides mobile users secure access to sensitive data. It can be used for secure online banking, e-Mail encryption or digital signatures. The reader is especially recommended for mobile use without any interfering cables.

The SCR241's patented design fits effortlessly into a standard PCMCIA Type II slot and offers an easy smart card insertion mechanism for your convenience. In addition, the SCR241 is the industry's first to offer on-board flash, allowing future firmware and application enhancements that guarantee against obsolescence.

SCR241 Benefits

- · Robust steel casing with easy smart card insertion mechanism
- Takes only one PCMCIA slot and can stay inserted even when traveling
- EMV Level 1 AND PC/SC certification based on a single solution
- · On-board flash provides seamless firmware upgrades in the field
- High performance
- Fully tested and compliant with all major smart cards in the market
- Branding option available

PC Security Solutions

U.S. Headquarters SCM Microsystems Inc. 41740 Christy Street Fremont, CA 94538 USA E-mail scmsales@scmmicro.com Phone +1 510 360 2300 Fax +1 510 360 0211

European Headquarters SCM Microsystems GmbH Oskar-Messter-Str. 13 85737 Ismaning, Germany E-mail sales@scmmicro.de Phone +49 89 9595 5000 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc. 8F Hirakawacho Ronstate, 2-11-1, Hirakawa-cho, Chiyoda-ku, Tokyo, Japan 102-0093 E-mail sales@scmmicro.co.jp Phone +81 3 3511 8511 Fax +81 3 3511 8516

SCM Microsystems India Pvt. Ltd. Module No. 0506, 0507 & 0508 D' Block South, 5th Floor Tidel Park, 4 Canal Bank Road Taramani Chennai 600113, India E-mail sales@scmmicro.co.in Phone +91 44 2254 0020 Fax +91 44 2254 0029











www.scmmicro.com



SCR241

Technical Data

Host Interface	PC-Card 8 bits I/O 5V PCMCIA Type II
Smart Card Interface	 T=0, T=1 protocol support Memory card support through SCM MCARD API Communication speed up to 344,105 bps (PPS, FI parameter) Frequency up to 8 MHz (PPS, DI parameter) Support ISO 7816 Class A and AB smart card
Smart Card Connector	8 contacts - ISO location100,000 insertionsSliding contact
Power	68 pins PCMCIA connectorPower through PCMCIA interface
Dimensions	• LWH 84.5 x 54 x 5 mm, weight 50 grams
Operating Temperature	o° to 50° Celsius
OS	 Windows® 98, ME, NT4, 2000, XP, CE, Vista Linux MacOS X
API	PC/SCCT-API (thru wrapper on top of PC/SC)OCF upon request
Approvals	FCC Class B part 15, cULus, CE, VCCI Microsoft® WHQL ME, 2000, XP EMV Level 1
Environmental	• RoHS • WEEE

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

SCM Microsystems brings over a decade of experience in ASIC and smart card reader development to this unique product. With its dedicated Research and Development team and a true global presence, SCM Microsystems delivers high quality products catering to the various requirements in the security field. SCM offers customization of products to suit application needs.

Typical advantages of an SCM Microsystems product include:

- More than 50 patents
- · High quality mass production capability
- Industry endorsed SmartOS™ middleware
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and smart card industry leaders
- Direct significant long-term relationships with all leading smart card manufacturers and application providers

